

HYUNDAI Line interactive UPS 500VA~1500VA



- AVR CPU, USB / RJ45 interface.
- Auto-self restart.
- Auto-self charge.
- Over charge & overload protection.
- Inbuilt battery 12V 7AH/9AH.

Series UPS Specification

MODEL		HD500L	HD600L	HD650L	HD800L	HD1000L	HD1200L	HD1500L	
Capacity(VA/W)		500VA/300W	600VA/360W	650VA/390W	800VA/480W	1000VA/600W	1200VA/720W	1500VA/900W	
INPUT									
Voltage	Nominal Voltage	110/115/120VAC or 220/230/240VAC							
	Acceptable Voltage Range	140-278 VAC				140-295 VAC			
OUTPUT									
Voltage		120VAC or 230VAC							
Voltage Range(Battery Mode)		10%							
Frequency		50Hz or 60Hz							
Frequency Regulation(Battery Mode)		+/-1 Hz							
Output Waveform		Modified Sine Wave							
BATTERY									
Battery Type and Number*		12V/7AHx1		12V/9AHx1		12V/7AHx2		12V/9AHx2	
Backup Time(at a PC load with 15"monitor)		15-20 minutes		20-25 minutes		30-35 minutes		40-45 minutes	45-50 minutes
Recharge Time		6 hours to 80%							
TRANSFER TIME									
Typical		2-6ms				4-8ms			
INDICATOR									
AC Mode		Green LED lighting							
Battery Mode		Yellow LED lighting							
Fault		Red LED lighting							
AUDIBLE ALARM									
Battery Mode		Beeping every 10 seconds							
Low Battery		Beeping every second							
Overload		Beeping every 0.5 second							
Battery replace		Beeping every 2 seconds							
Fault		Continuously Beeping							
PROTECTION									
Full Protection		Discharge,Overcharge,and Overload Protection			Discharge,Overcharge,Short-Circuit and Overload Protection				
PHYSICAL									
Dimension DxWxH(mm)		330x95x140				330x120x185			
Dimension DxWxH(mm)		380x300x460(4pcs)				415x405x280(2pcs)			
Net Weight(kgs)		5.0	5.5	6.0	6.8	10	10.5	11	
Operating Environment		0-40°C,0-90% Relative humidity (non-condensing)							
Noise Level		Less than 40dB				Less than 45dB			
INTERFACE									
USB Option		Windows family and MAC OS							

* Product specifications are subject to change without further notice.